CarriArt Shoulder Strap Fitting Instructions

Overview

CarriArt shoulder straps are designed to be easily added or removed.

The following instructions apply when fitting the shoulder strap to an *ArtCase* carrier. For removal simply reverse the order of the instructions.

Parts

To fit the shoulder strap the following parts are required:

- 1x shoulder strap
- 2x strap attachments
- 2x male binder screws
- 2x female binder screws

Note: The two part of the binder screw can be identified by the difference between the shanks (the long thin part). On the male binder screw the shank is threaded on the outside, while on the female it is smooth.

Orientation

The strap is fitted to the carrier via two strap attachments. The strap attachments are fastened to the sides of the carrier via small holes. The holes are in the sides of the carrier base, towards the front (where the handle is fitted).

Binder screws are supplied with each *ArtCase* set. Where no strap is fitted the binder screws are used to fill the holes punched during manufacture, while also ensuring the carrier is as air-tight and dust-proof as possible. In case the originals have been lost, spares are provided with the accessory strap kit.

Fitting

The following instructions assume that the binder screws are already fitted to the carrier. Work from outside the carrier, repeating the steps for each side.

SS.1	**Unscrew and remove the male binder screws**	Undo the male binder screw by turning the head anti-clockwise. (Retain the removed screw for refitting.)
SS.2	**Position the strap attachment**	Push the shank of the male binder screw through the hole in the strap attachment. Position the tip of the male binder screw against where the female part of the screw appears in the side of the base.
SS.3	**Screw the binder screws into position**	Screw the male part of the binder screw into the female part of the binder screw, turning the male part clockwise. Tighten the binder screw to prevent it coming undone.
SS.4	**Clip the strap in place**	Clip the G-hook on the strap over the D-hoop on the strap attachment.

Note: If needed use the slots in the heads of the binder screws and a flat-blade screw-driver to slacken or tighten the screws.

Maintenance

With prolonged use the screws may become loose, leading to the strap attachments coming away from the carrier.

We recommend checking the tightness of the screws every three months or so to ensure they are not loose. The binder screws can be tightened either by hand or by the slot in the head of each screw using a screw-driver.

Support

Warranty

Each CarriArt product is guaranteed against manufacturing defects for one year from the date of purchase. If you wish to claim under this warranty please contact us via one of the methods shown under the Contact Details section below.

Where possible we will try to help outside of the warranty period, so please contact us if you have any questions either now or in the future.

Questions & Feedback

The CarriArt website (www.carriart.co.uk) carries a Frequently Asked Questions section which we update as new queries arise.

We welcome feedback on CarriArt products.

Contact Details

If you have a question or feedback, please email us at: support@carriart.co.uk.

Alternatively we can be contacted via post at:

CarriArt
3 Hill View
Dorton
Aylesbury
Buckinghamshire
HP18 9NJ

Copyright

All designs and materials © 2013-18 Doug Smith trading as CarriArt.

Patent applied for the design of the holders 2013.

Should Strap Fitting Instructions v1.3 (July 2018).